
## LEGEND

LEGEND					
EXISTING	PROPOSED	DESCRIPTION	EXISTING	PROPOSED	DESCRIPTION
		EDGE OF PAVEMENT	D	<del></del>	REDUCER
CURB		CURB AND GUTTER			FENCE
		EDGE OF GRAVEL		~ ~ ~	DITCH/SWALE
ТВ/ВВ		TOP/BOTTOM OF BANK	W		WATERMAIN (SIZE AND MATERIAL NOTED)
		CATCH BASIN		s ———	SANITARY SEWER (SIZE AND MATERIAL NOTED)
	<del></del>	WATER VALVE	D	D —	STORM DRAIN (SIZE AND MATERIAL NOTED)
-Ó-FH	<b>*</b>	FIRE HYDRANT	Т——Т	T —	UNDERGROUND TELEPHONE
		CAPPED END	Н	Н ———	UNDERGROUND HYDRO
$\ominus$		UTILITY POLE AND STREET LIGHT (LABELED PP,TP,PP/LS ETC.)	$\odot$		MONUMENT
	<b>—</b>	MANHOLE			PROPERTY LINE
———⊗ <sup>CO</sup>	<b>~</b>	CLEANOUT		5+100 5+110	CENTERLINE AND STATIONING
SSIC/SDIC	SSIC/SDIC	SANITARY/STORM INSPECTION CHAMBER (2000 RISER)	<i>y</i>		SANITARY SEWER SERVICE CONNECTION AT MAIN
JB		JUNCTION BOX	+32.75	43.170)+	ELEVATIONS
	<b>(3)</b>	AIR VALVE			PAVEMENT REMOVAL
WM		WATER METER			NEW ASPHALT

## LIST OF DRAWINGS

RDN DWG No.	DWG No.	DESCRIPTION
GN-GEN-G-221	C01	KEY PLAN, DRAWING LIST, & GENERAL NOTE
CN-C-GEN-221	C02	PROPOSED TRAILWAY - PLAN/PROFILE STA. 3+000 TO 3+150
CN-C-GEN-222	C03	PROPOSED TRAILWAY - PLAN/PROFILE STA. 3+150 TO 3+300
CN-C-GEN-223	C04	PROPOSED TRAILWAY - PLAN/PROFILE STA. 3+300 TO 3+420
CN-C-GEN-224	C05	TYPICAL CROSS SECTIONS
CN-C-GEN-225	C06	EROSION & SEDIMENT CONTROL PLAN
CN-C-GEN-226	XS-1	CROSS SECTIONS STA. 3+010 TO 3+100
CN-C-GEN-227	XS-2	CROSS SECTIONS STA. 3+110 TO 3+200
CN-C-GEN-228	XS-3	CROSS SECTIONS STA. 3+210 TO 3+300
CN-C-GEN-229	XS-4	CROSS SECTIONS STA. 3+310 TO 3+420
CN-E-GEN-221	E1	STREET LIGHTING LAYOUT
CN-L-GEN-221	L1	LANDSCAPE PLANTING
CN-L-GEN-222	I1	IRRIGATION PLAN
CN-L-GEN-223	12	IRRIGATION DETAILS



LOCATION PLAN NTS

## **GENERAL NOTES:**

- 1. ALL WORK AND MATERIALS ARE TO BE AS DESCRIBED IN THE CITY OF NANAIMO ENGINEERING STANDARDS & SPECIFICATIONS LATEST EDITION (No. 12, NOVEMBER 2019) OR AS OTHERWISE APPROVED BY THE CITY ENGINEER.
- 2. CONNECTION TO, OR ALTERATION OF, EXISTING CITY—OWNED UTILITIES, REQUIRES AUTHORIZATION BY THE CITY ENGINEER.
- 3. A "PERMIT TO INSTALL WORKS WITHIN STREETS, LANES AND CITY PROPERTY AREAS" WILL BE REQUIRED WHERE CONSTRUCTION IS TO BE UNDERTAKEN IN CITY OF NANAIMO RIGHT-OF-WAYS AND/OR CITY OF NANAIMO-OWNED UTILITIES OR PROPERTIES.
- 4. UPON APPROVAL OF THE PERMIT, THE CITY OF NANAIMO'S CONSTRUCTION DIVISION SHALL BE NOTIFIED 48 HOURS PRIOR TO COMMENCEMENT OF WORK.
- THE ENGINEER SHALL BE NOTIFIED 48 HOURS PRIOR TO COMMENCEMENT OF WORK.
   CONTRACTOR TO COMPLY WITH ALL APPLICABLE MINISTRY OF ENVIRONMENT AND DEPARTMENT OF FISHERIES & OCEANS CANADA REQUIREMENTS AT ALL TIMES DURING
- 7. CONTRACTOR TO CONFIRM LOCATION OF EXISTING UTILITIES AT ALL CROSSINGS AND CONNECTIONS AND REPORT ANY DISCREPANCIES TO THE ENGINEER PRIOR TO
- CONSTRUCTION.

  8. CONTRACTOR TO CONFIRM THAT ELEVATION, LOCATION AND GRADIENT OF ASPHALT MATCH
- EXISTING PRIOR TO PLACEMENT OF ASPHALT OR CONCRETE.

  9. ALL TREES NOT BEING REMOVED IN THE CONSTRUCTION AREA SHALL BE PROTECTED.

  10. TREE REMOVAL PERMIT REQUIRED BY OTHERS.
- 11. ADJUST ALL MANHOLES, WATER VALVES, HYDRO VAULTS, ETC. TO MATCH NEW CONSTRUCTION.
- 12. ALL LOCATIONS AND ELEVATIONS OF EXISTING UTILITIES SHOWN ARE APPROXIMATE ONLY AND SHOULD BE CONFIRMED BY USE OF A PIPE LOCATOR AND MANUAL DIGGING. ALL OR ANY STRUCTURES NOT NECESSARILY SHOWN.
- 13. ALL ELEVATIONS ARE TO GEODETIC DATUM AND ARE REFERENCED TO MONUMENT 82H5677 AT THE INTERSECTION OF MCGUFFIE ROAD & HAMMOND BAY ROAD. ELEVATION = 31.807. 14. DATA SOURCES:
- -TOPOGRAPHIC SURVEY COMPLETED BY 3D GEOMATICS IN JUNE 2017. -ASBUILTS PROVIDED BY THE CITY OF NANAIMO.

## ROAD NOTES:

LOT A 1001 MORNINGSIDE DRIVE

TIKI WAY

1. ALL CURB AND GUTTER TO BE C.O.N. TYPE CS-1 UNLESS OTHERWISE NOTED.

## PRIVATE UTILITY NOTES:

- GAS MAIN AND SERVICE LOCATIONS ARE APPROXIMATE ONLY AND ARE BASED ON FORTIS BC INFORMATION.
- 2. BC HYDRO TELUS AND SHAW CABLE INFORMATION IS BASED ON BCONE CALL INFORMATION

## STORM SEWER NOTES:

- 1 ALL CATCH BASINS TO BE CONTYPE 1 LINESS OTHERWISE NOTED
- ALL CATCH BASINS TO BE C.O.N. TYPE 1 UNLESS OTHERWISE NOTED.
   ALL CATCH BASIN LEADS TO BE 200¢ PVC SDR35 UNLESS OTHERWISE NOTED.

SSUED FOR TENDER

No. DATE WYMALD ISSUED FOR

A 2017.07.28 ISSUED FOR 75% REVIEW

B 2017.08.31 ISSUED FOR 95% REVIEW

C 2017.09.07 BUS PULLOUT ADDED

D 2017.10.24 ISSUED FOR APPROVAL

E 2019.12.13 ISSUED FOR DSA

F 2020.03.31 ISSUED FOR TENDER

GREATER NANAIMO POLLUTION CONTROL CENTR FRONTAGE WORKS

m

ANAIMO,

## HEROLD ENGINEERING 701 Shenton Rd, Nanaimo, BC V9T 2H1

Tel: 250-751-8558 Fax: 250-751-8559

Email: mail@heroldengineering.com

©Copyright reserved. This drawing remains the exclusive property of Herold Engineering Limited and may not be reused or reproduced without written consent of Herold Engineering Limited.

KEY PLAN,
DRAWING LIST,

& GENERAL NOTES

DESIGNED ENGINEER'S SEAL


DESIGN REVIEW
PGR


DRAFTED
EGAP


DRAFTING REVIEW
PGR


PGR


PROJECT No. | RDN DRAWING No. |
0837-047 | GN-GEN-G-221 |
SCALE | PERMIT No. |
H: 1:1000 | ENG01365/BP123











## **EROSION & SEDIMENT CONTROL NOTES:**

- EROSION AND SEDIMENT CONTROL FOR THIS PROJECT WILL BE AS OUTLINED IN THE FISHERIES AND OCEANS CANADA & MINISTRY OF WATER, LANDS AND AIR PROTECTION HANDBOOK ENTITLED "LAND DEVELOPMENT GUIDELINES FOR THE PROTECTION OF THE AQUATIC HABITAT, SEPTEMBER 1993" AND "ENVIRONMENTAL BEST MANAGEMENT PRACTICES FOR URBAN AND RURAL LAND DEVELOPMENT IN BRITISH COLUMBIA, JUNE 2004" AND "EROSION & SEDIMENT CONTROL GUIDELINE" BY THE CITY OF NANAIMO. IT IS INCUMBENT UPON THE CONTRACTOR TO ACQUIRE THESE GUIDELINES AND FAMILIARIZE HIMSELF WITH THE REQUIREMENTS WITHIN.
- 2. THE CONSULTANT ASSUMES NO RESPONSIBILITY FOR DAMAGES RESULTING FROM IMPROPER EROSION AND SEDIMENT CONTROL MEASURES UNDERTAKEN BY THE
- 3. ANY DIRECTION GIVEN BY THE CONSULTANT OR CITY TO THE CONTRACTOR FOR EROSION AND SEDIMENT CONTROL AND NOT FOLLOWED BY THE CONTRACTOR IS TO BE REPORTED TO THE CITY IMMEDIATELY.
- 4. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ENSURE NO MUD, DIRT, SOIL, SILT OR ANY OTHER SUBSTANCES ARE SPILLED, DROPPED, WASHED OR TRACKED ONTO PUBLIC RIGHTS OF WAY, OR AREAS THAT LEAD TO CATCH BASINS CONNECTED TO PUBLIC SYSTEMS. THE CONTRACTOR IS TO CLEAN ANY SUCH MATERIAL IMMEDIATELY. i.e. STREETS ARE TO BE SWEPT WITH A VACUUM STREET SWEEPER AFTER WORK STOPPAGE EACH DAY.
- 5. PRIOR TO CONSTRUCTION, INSTALL A TEMPORARY GRAVEL CONSTRUCTION ENTRANCE/EXIT TO LIMIT TRACKING OF SITE SOILS ONTO OFFSITE ROADWAYS. THE WIDTH OF THE PAD SHOULD NOT BE LESS THAN THE FULL WIDTH OF POINT OF INGRESS OR EGRESS IN ANY CASE SHOULD NOT BE LESS THAN 6m WIDE WITH A LENGTH OF THE PAD NOT LESS THAN 20m AND HAVING A MINIMUM THICKNESS OF 200mm (8") OF COARSE GRANULAR MATERIAL. COARSE GRANULAR MATERIAL SUCH AS 75mm PLUS SHOT ROCK OR FRACTURED DRAIN ROCK UNDERLAIN WITH GEO-TEXTILE FABRIC IS RECOMMENDED.
- 6. THE ENTRANCE SHOULD BE MAINTAINED FOR THE DURATION OF CONSTRUCTION, IN A CONDITION THAT WILL PREVENT TRACKING OF SEDIMENT ONTO PUBLIC RIGHT OF WAYS, OR AREAS THAT LEAD TO CATCH BASINS CONNECTED TO PUBLIC SYSTEMS. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL MATERIAL AS CONDITIONS DEMAND. THE PAD MAY BE REMOVED ONCE PERMANENT PAVEMENTS ARE IN PLACE AT THE SITE. A WHEEL WASH MAY BE REQUIRED IF THE TEMPORARY GRAVEL PAD IS NOT WORKING.
- 7. PRIOR TO CONSTRUCTION, CONTRACTOR TO CLEARLY FLAG OR FENCE AREAS OF NO DISTURBANCE AS WELL AS ANY DESIGNATED TREES AND SHRUBS THAT ARE TO BE PRESERVED. MARKINGS SHALL REMAIN IN PLACE THROUGHOUT CONSTRUCTION.
- 8. CONTRACTOR TO STRIP AND GRUB ONLY THOSE AREAS NECESSARY FOR THE CURRENT CONSTRUCTION. STAGE CONSTRUCTION OPERATIONS TO LIMIT DISTURBANCE AND DO NOT STRIP ANY AREA UNTIL REQUIRED.
- 9. GRADE WORK AREAS AWAY FROM ADJACENT PROPERTIES AND TOWARDS THE SEDIMENT POND ON THE SITE FOR DISPERSAL INFILTRATION.
- 10. REVEGETATION OPERATIONS SHOULD BE CARRIED OUT WITHIN ONE WEEK OF GRADING COMPLETION OR NO LATER THAN SEPT. 15th.
- 11. SILT FENCING IS TO BE INSTALLED AROUND ALL STOCK/SPOIL PILES, OR PILES ARE TO BE OTHERWISE COVERED TO LIMIT EROSION AND SEDIMENT GENERATION.
- 12. WHEN SHOWN ON THE CONTRACT DRAWINGS, CONTRACTOR TO INSTALL SETTLEMENT PONDS EQUIPPED WITH EMERGENCY OVERFLOW, FOR RETENTION/INFILTRATION TREATMENT OF RUNOFF COLLECTED BY INTERCEPTOR SWALES (DITCHES) AND/OR SILT BARRIERS. THE SETTLEMENT PONDS ARE TO HAVE A MINIMUM VOLUME TO CONTAIN FLOWS FROM A 10-YEAR RETURN PERIOD, 24-HOUR RAINFALL EVENT. THE PONDS SHOULD BE USED AND MAINTAINED THROUGHOUT THE DURATION OF CONSTRUCTION.
- 13. ROUTINE INSPECTION AND MAINTENANCE OF THE SYSTEM COMPONENTS WILL BE THE RESPONSIBILITY OF THE CONTRACTOR. THE CONTRACTOR SHOULD DESIGNATE AN ON-SITE PERSON TO BE RESPONSIBLE FOR DAY-TO-DAY MANAGEMENT OF THE ESCP. AT A MINIMUM, INSPECT ALL BMP'S WEEKLY TO ENSURE PROPER FUNCTION WITH INSPECTION REPORTS PROVIDED TO THE ENGINEER AND THE CITY OF NANAIMO FOR REVIEW.
- 14. 48 HOURS PRIOR TO ANY PREDICTED SIGNIFICANT STORM EVENT, THE DESIGNATED SITE PERSON SHOULD INSPECT THE E&SC WORKS AND ENSURE THAT THE WORKS ARE ADEQUATE TO PROTECT THE SITE DURING THE STORM EVENT AND PROVIDE A WRITTEN REPORT TO THE ENGINEER AND/OR THE CITY UPON REQUEST. IF THE DESIGNATED SITE PERSON DETERMINES THAT THE E&SC WORKS ARE NOT ADEQUATE TO PROTECT THE SITE DURING THE ANTICIPATED STORM EVENT, THEN HE/SHE IS TO IMMEDIATELY INFORM THE ENGINEER AND CONTRACTOR SO THAT THE WORKS CAN BE MODIFIED TO ADEQUATELY PROTECT THE SITE DURING THE STORM EVENT AND PROVIDE A WRITTEN REPORT TO THE ENGINEER AND/OR THE CITY UPON REQUEST.
- 15. DURING AND/OR FOLLOWING EACH SIGNIFICANT STORM EVENT, THE DESIGNATED SITE PERSON SHOULD OBSERVE THE SETTLEMENT PONDS AND STORM DRAIN TO CONFIRM THAT TURBID WATERS FROM SOURCES ASSOCIATED WITH CONSTRUCTION ARE NOT ENTERING THE STORM DRAINAGE SYSTEM. TAKE IMMEDIATE CORRECTIVE ACTION IF INSPECTION INDICATES A PROBLEM. RECORD INSPECTION DATES, ANY SIGNIFICANT OBSERVATIONS, AND ACTIONS TAKEN, THEN INFORM THE CONSULTANT IN CHARGE AND THE CITY OF NANAIMO.
- 16. CITY OF NANAIMO STANDARD EROSION & SEDIMENT CONTROL SIGNAGE IS REQUIRED TO BE PLACED ON-SITE PRIOR TO THE START OF CONSTRUCTION AND MAINTAINED IN PLACE UNTIL LANDSCAPING IS COMPLETED.

## <u>LEGEND</u>

OVERLAND FLOW

TEMPORARY SILT FENCE

ISSUES

No. DATE YYYY.MM.DD ISSUED FOR A 2017.07.28 ISSUED FOR 75% REVIEW

B 2017.08.31 ISSUED FOR 95% REVIEW

C 2017.09.07 BUS PULLOUT ADDED D 2017.10.24 ISSUED FOR APPROVAL

2019.12.13 ISSUED FOR DSA 2020.03.31 ISSUED FOR TENDER

. И

 $\mathsf{O}$ 0 SREATI RONT (D)

3701 Shenton Rd, Nanaimo, BC V9T 2H Tel: 250-751-8558 Fax: 250-751-8559

Email: mail@heroldengineering.com

AD

©Copyright reserved. This drawing remains the exclusive property of Herold Engineering Limited and may not be reused or reproduced without written consent of Herold Engineering Limited. **EROSION & SEDIMENT CONTROL PLAN** 

ENGINEER'S SEAL

# 34339

EGAP DESIGN REVIEW


HEL DRAWING No.

PGR DRAFTED EGAP

DRAFTING REVIEW PGR

PROJECT No. RDN DRAWING No. 0837-047 GN-C-GEN-225 SCALE PERMIT No. ENG01365/BP123009

C06 6 **or** 10 DESTROY ALL DRAWINGS SHOWING PREVIOUS REVISION




7 **or** 10 DESTROY ALL DRAWINGS SHOWING PREVIOUS REVISION

ENGINEER'S SEAL

GN-C-GEN-226

ENG01365/BP123009

PERMIT No.



ISSUES No. DATE YYYY.MM.DD ISSUED FOR A 2017.07.28 ISSUED FOR 75% REVIEW
B 2017.08.31 ISSUED FOR 95% REVIEW
C 2017.09.07 BUS PULLOUT ADDED
D 2017.10.24 ISSUED FOR APPROVAL
E 2019.12.13 ISSUED FOR DSA
F 2020.03.31 ISSUED FOR TENDER

ANAIMO, BC

Tel: 250-751-8558 Fax: 250-751-8559 Email: mail@heroldengineering.com ©Copyright reserved. This drawing remains the exclusive property of Herold Engineering Limited and may not be reused or reproduced without written consent of Herold Engineering Limited.

CROSS SECTIONS STA. 3+110 TO 3+200

ENGINEER'S SEAL


DESIGN REVIEW

DRAFTING REVIEW


0837-047 GN-C-GEN-227 ENG01365/BP123009

HEL DRAWING No. XS-2 8 **or** 10

DESTROY ALL DRAWINGS SHOWING PREVIOUS REVISION



DESTROY ALL DRAWINGS SHOWING PREVIOUS REVISION



ISSUES No. DATE WWW.MM.DD ISSUED FOR A 2017.07.28 ISSUED FOR 75% REVIEW
B 2017.08.31 ISSUED FOR 95% REVIEW
C 2017.09.07 BUS PULLOUT ADDED
D 2017.10.24 ISSUED FOR APPROVAL
E 2019.12.13 ISSUED FOR DSA
F 2020.03.31 ISSUED FOR TENDER

CENTRE

Tel: 250-751-8558 Fax: 250-751-8559 Email: mail@heroldengineering.com ©Copyright reserved. This drawing remains the exclusive property of Herold Engineering Limited and may not be reused or reproduced without written consent of Herold Engineering Limited.

**CROSS SECTIONS** STA. 3+310 TO 3+420

EGAP DESIGN REVIEW PGR

EGAP DRAFTING REVIEW


PGR

ENGINEER'S SEAL

PROJECT No. GN-C-GEN-229 0837-047 PERMIT No.

ENG01365/BP123009 HEL DRAWING No. 10 **or** 10

DESTROY ALL DRAWINGS SHOWING PREVIOUS REVISION



- 1. THE ELECTRICAL CONTRACTOR SHALL SUPPLY ALL LABOUR, MATERIALS, TOOLS, EQUIPMENT, TRANSPORTATION REQUIRED FOR THE COMPLETE INSTALLATION, WIRING AND TESTING OF THE SYSTEM SHOWN ON THE DRAWINGS AND DESCRIBED HEREIN & IS RESPONSIBLE TO REVIEW CIVIL DRAWINGS FOR DISCREPANCIES AND REPORT TO THE ENGINEER
- 2. THE ELECTRICAL DRAWINGS INDICATE THE GENERAL LOCATION AND ROUTE. CONDUIT AND/OR WIRING SHALL BE INSTALLED TO PROVIDE A COMPLETE OPERATING SYSTEM.
- 3. THE WORK TO BE DONE IS DESCRIBED IN THE DRAWINGS.
- 4. THE DRAWINGS AND SPECIFICATIONS COMPLEMENT EACH OTHER AND WHAT IS CALLED FOR BY ONE IS BINDING AS IF CALLED FOR BY BOTH, IF THERE IS ANY DOUBT AS TO THE MEANING OR TRUE INTENT DUE TO A DISCREPANCY BETWEEN THE DRAWINGS AND SPECIFICATIONS, OBTAIN RULING FROM ENGINEER PRIOR TO TENDER CLOSING. FAILING THIS, ALLOW FOR THE MOST EXPENSIVE ALTERNATIVE.
- 5. ELECTRICAL DRAWINGS ARE DIAGRAMMATIC AND DO NOT SHOW ALL CONDUIT, WIRE, CABLE, ETC., THE ELECTRICAL CONTRACTOR IS TO PROVIDE CONDUIT, WIRE, CABLE, ETC. FOR A COMPLETE OPERATING JOB TO MEET IN ALL RESPECTS THE INTENT OF THE DRAWINGS AND SPECIFICATIONS. ELECTRICAL DRAWINGS DO NOT SHOW ALL CIVIL DETAILS.
- 6. IT IS THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO DETERMINE AS TO WHICH SUBCONTRACTOR PROVIDES SPECIFIC LABOUR AND MATERIALS. EXTRAS WILL NOT BE CONSIDERED BASED ON DIFFERENCES IN INTERPRETATION AS TO WHICH TRADE IS TO PROVIDE CERTAIN ITEMS.

## PERMITS, CERTIFICATES, AND FEES

- 1. ON COMPLETION OF THE WORK, SUBMIT CERTIFICATE OF ACCEPTANCE FROM INSPECTION AUTHORITY TO THE ENGINEER.
- 2. PRIOR TO COMMENCEMENT OF WORK, SUBMIT THE NECESSARY DRAWINGS TO THE ELECTRICAL INSPECTION DEPARTMENT AND THE ELECTRICAL SUPPLY AUTHORITY.
- 3. PAY ALL ASSOCIATED FEES, AND OBTAIN DOCUMENTS POSTING AS REQUIRED.

## STREET LIGHTING

- 1. ALL STREET LIGHT CONSTRUCTION TO CONFORM TO THE CITY OF NANAIMO STANDARDS AND SPECIFICATIONS FOR STREET LIGHTING DESIGN AND CONSTRUCTION.
- 2. TYPE 'A' POLES TO BE ROADWAY, 5.8m IN TOTAL HEIGHT, ONE PIECE OCTAGONAL TAPERED, STEEL, 1.8m DAVIT ARM c/w GALVANIZED FINISH.
- 3. TYPE 'A' LED STREET LIGHT LUMINAIRE TO BE CITY OF NANAIMO 150 WATT HPS, TYPE 3 REPLACEMENT:
- .1 AMERICAN ELECTRIC LIGHTING ATBO-30BLEDE13-MVOLT-R3, OR .2 EATON VERDEON VERD-C02-U-T3-AP
- 4. TYPE 'B' POLES TO BE ROADWAY, 9.14m IN TOTAL HEIGHT, ONE PIECE OCTAGONAL
- TAPERED, STEEL, 2.4m DAVIT ARM c/w GALVANIZED FINISH. 5. TYPE 'B' LED STREET LIGHT LUMINAIRE TO BE CITY OF NANAIMO 100 WATT HPS, TYPE 3
- .1 AMERICAN ELECTRIC LIGHTING ATBO-20BLEDE10-MVOLT-R3, OR
- .2 EATON VERDEON VERD-C018-U-T3-AP 6. STREET LIGHTS TO BE COMPLETE WITH NEMA LABEL INDICATING LUMINAIRE WATTAGE AND
- SHORTING CAP WHERE REQUIRED.
- 7. STREET LIGHTS TO ALTERNATE BETWEEN THE BLACK AND RED PHASE. 8. STREET LIGHT WIRING TO BE #4 AWG AL RW90 AND #6 AWG AL RW90 BOND, TO BE CONTAINED IN A 41mm (1 1/2") RIGID PVC CONDUIT. LUMINAIRE WIRING TO BE #14 AWG CU RW90 c/w #12 AWG CU RW90 BOND IN STREET LIGHT POLE. GROUND CONDUCTOR TO BE #6 AWG CU RW90.
- 9. ALL ALUMINUM TERMINATIONS SHALL USE ANTI-OXIDATION COMPOUND AND USE COPPER/ALUMINUM RATED SPLICE HARDWARE FOR ALL CU/AL CONNECTIONS AS PER CANADIÁN ELECTRICAL CODE REQUIREMENTS.
- 10. PROVIDE A 53mm RIGID PVC CONDUIT c/w SERVICE CONDUCTORS TO BC HYDRO AND CITY OF NANAIMO SPECIFICATIONS FROM THE BC HYDRO SERVICE TO THE STREET LIGHT SERVICE
- 11. SERVICE BASES TO BE 60 AMP, 120/240 VOLT, SINGLE PHASE. SERVICE BASE TO CONTAIN CONTACTORS AND HOA SWITCH AND BE 915mm IN HEIGHT. SERVICE EQUIPMENT TO BE ENCLOSED IN ONE NEMA 3R, CSA APPROVED COMPREHENSIVE ENCLOSURE MANUFACTURED BY WEST COAST ELECTRIC, VALID MANUFACTURING OR APPROVED EQUAL.
- 12. STREET LIGHT ON SERVICE BASE TO BE 4.88m IN HEIGHT AND CONTAIN THE PHOTOCELL
- 13. STREET LIGHTS TO HAVE A BUSMAN 10 AMP INLINE FUSE. 14. PROVIDE PULL STRINGS IN ALL EMPTY CONDUIT.
- 15. CONTRACTOR TO ALLOW FOR ONE VISIT TO SITE WITH RB ENGINEERING AFTER CONSTRUCTION IS COMPLETE FOR FINAL INSPECTION. CONTRACTOR TO CALL FOR INSPECTION ONCE SYSTEM INSTALLATION HAS BEEN COMPLETED AND ENERGIZED BY BC HYDRO. ADDITIONAL VISITS MAY BE REQUIRED IF DEFICIENCIES ARE FOUND.
- 16. CONTRACTOR TO COORDINATE WITH CITY OF NANAIMO AND BC HYDRO FOR SERVICE CONNECTION FOR THE STREET LIGHTS.
- 17. PRIOR TO INSTALLATION OF STREET LIGHTS CONTRACTOR IS TO SUBMIT AT COST AUTHORIZATION FORM TO THE CITY OF NANAIMO TO COORDINATE THE INSTALLATION OF LOCKING HAND HOLE COVERS. CONTRACTOR TO ADVISE MUNICIPAL INSPECTOR 72 HOURS PRIOR TO INSTALLATION OF STREET LIGHT CONDUCTORS TO ALLOW THE CITY OF NANAIMO TO COORDINATE INSTALLATION OF LOCKING HAND HOLE COVERS.
- 18. IF OVERHEAD UTILITIES ARE PRESENT CONTRACTOR SHALL ENSURE THAT REQUIRED CLEARANCES ARE MET. ONCE LIGHT POLE BASES HAVE BEEN INSTALLED AND BEFORE INSTALLING STREET LIGHT POLES CONTRACTOR SHALL COORDINATE WITH CIVIL ENGINEER TO SURVEY REQUIRED BC HYDRO CLEARANCES (1 METRE FROM SECONDARY WIRING, 3 METRES FROM PRIMARY WIRING) AND REPORT CONFLICTS TO THE ENGINEER.

5.8m STREET LIGHT - 90W LED COBRA-HEAD 9.14m STREET LIGHT - 50W LED COBRA-HEAD ● ★ (FUTURE) 9.14m FUTURE STREET LIGHT (NOT IN CONTRACT) ● ★ (EXISTING) 9.14m EXISTING STREET LIGHT


EXISTING BC HYDRO LEASE LIGHT BURIED STREET LIGHT CONDUIT

TYPICAL JUNCTION

SCALE: N.T.S.

**BOX DETAIL** 

EXISTING STREET LIGHT CONDUIT STREET LIGHT CONDUIT STUB STREET LIGHTING JUNCTION BOX



TYPE 'B' STREET LIGHT POLE SCALE: N.T.S.

## HAMMOND BAY ROAD

**DESIGN CRITERIA** .1 ROAD CLASSIFICATION : MAJOR COLLECTOR .2 AVERAGE ILLUMINATION : 12 LUX .3 UNIFORMITY RATIO : 3:1 4 POLE HEIGHT .5 DAVIT ARM : 1.8m & 2.4m .6 LIGHT DISTRIBUTION : TYPE 3 : EATON VERDEON LED : 90W LED .9 MAINTENANCE FACTOR : 0.79 DESIGN CALC

.1 AVERAGE ILLUMINATION : 14.671 : 4.8 LUX

.2 MIN. ILLUMINATION .3 UNIFORMITY RATIO : 3.0:1

> 1830mm 5792mm CONCRETE BASE

TYPE 'A' STREET LIGHT POLE SCALE: N.T.S.

## **WALKWAY**

.3 UNIFORMITY RATIO

DESIGN CRITERIA .1 ROAD CLASSIFICATION : WALKWAY AVERAGE ILLUMINATION : 4 LUX .3 UNIFORMITY RATIO : 6:1 POLE HEIGHT .5 DAVIT ARM : 1.8m & 2.4m .6 LIGHT DISTRIBUTION : TYPE 3 .7 LUMINAIRE : EATON VERDEON LED .8 LAMP : 90W LED .9 MAINTENANCE FACTOR : 0.79 DESIGN CALC .1 AVERAGE ILLUMINATION : 5.94 LUX .2 MIN. ILLUMINATION : 1.4 LUX

## INTERSECTION OF HAMMOND BAY RD. & MCGUFFIE RD.

: 4.24:1

DE:	DESIGN CRITERIA								
<b>.1</b>	ROAD CLASSIFICATION	:	MAJOR COLLECTOR & NEIGHBOURHOOD COLLECTOR						
.2	AVERAGE ILLUMINATION	:	21 LUX						
.3	UNIFORMITY RATIO	:	3:1						
.4	POLE HEIGHT	:	5.8m & 9.14m						
.5	DAVIT ARM	:	1.8m & 2.4m						
.6	LIGHT DISTRIBUTION	:	TYPE 2 & 3						
.7	LUMINAIRE	:	EATON VERDEON LED						
.8	LAMP	:	90W LED						
.9	MAINTENANCE FACTOR	:	0.79						
DE	SIGN CALC								
.1	AVERAGE ILLUMINATION	:	21.02 LUX						
.2	MIN. ILLUMINATION	:	12.6 LUX						
.3	UNIFORMITY RATIO	:	1.67:1						

## SHORES DRIVE

DE	SIGN CRITERIA		
.1	ROAD CLASSIFICATION	:	URBAN LOCAL
.2	AVERAGE ILLUMINATION	:	6 LUX
.3	UNIFORMITY RATIO	:	6:1
.4	POLE HEIGHT	:	9.14m
.5	DAVIT ARM	:	2.4m
.6	LIGHT DISTRIBUTION	:	TYPE 3
.7	LUMINAIRE	:	EATON VERDEON LED
.8	LAMP	:	55W LED
.9	MAINTENANCE FACTOR	:	0.79
DE	SIGN CALC		
.1	AVERAGE ILLUMINATION	:	7.5 LUX
.2	MIN. ILLUMINATION	:	1.3 LUX
.3	UNIFORMITY RATIO	:	5.77:1

## INTERSECTION OF HAMMOND BAY RD. & TIKI WAY/SHORES DR.

			<u> </u>
DE:	SIGN CRITERIA		
.1	ROAD CLASSIFICATION	:	MAJOR COLLECTOR & NEIGHBOURHOOD COLLECTOR
.2	AVERAGE ILLUMINATION	:	21 LUX
.3	UNIFORMITY RATIO	:	3:1
.4	POLE HEIGHT	:	5.8m & 9.14m
.5	DAVIT ARM	:	1.8m & 2.4m
.6	LIGHT DISTRIBUTION	:	TYPE 3
.7	LUMINAIRE	:	EATON VERDEON LED
.8	LAMP	:	90W LED
.9	MAINTENANCE FACTOR	:	0.79
DE:	SIGN CALC		
.1	AVERAGE ILLUMINATION	:	21.5 LUX
.2	MIN. ILLUMINATION	:	6.9 LUX
.3	UNIFORMITY RATIO	:	3.1:1

**GREATER NANAIMO POLLUTION** 

05 ISSUED FOR REVIEW

28 ISSUED FOR 75% REVIEW

COMMENT

REVISION

RB ENGINEERING LTD

TEL 250-756-4444

RBENGINEERING.CA

#4 1850 NORTHFIELD ROAD

NANAIMO, BC, V9S 3B3

2017

2017

NO. DATE

CLIENT

PROJECT

**CONTROL CENTRE** 


STREET LIGHTING LAYOUT

PROJECT NO. 17-2584 JULY, 2017 SCALE

1:500 DRAWING NO.

CITY OF NANAIMO FILE No. ENG01365/BP123005 CITY OF NANAIMO DRAWING No.

RDN DWG. No. GN-E-GEN-221



**GREATER NANAIMO** POLLUTION CONTROL CENTRE

LANDSCAPE PLANTING

PROJECT ADDRESS: 4600 Hammond Bay Rd, Nanaimo, BC V9T 5A8

MEMBER Jessica Gemella

NOTES
DROUGHT TOLERANT
SEED AT SUPPLIERS
RECOMMENDED RATE


Copyright Reserved. This drawing is, and shall remain the exclusive property Gemella Design Inc. and may not be used without the written consent of J. Gemella, Landscape Architect.


Issi	ues & Re	evisions
No.	Date	Details
#	D/M/YEAR	
1	10 19 2017	100% SUBMISSION


LANDSCAPE ARCHITECTURE GREEN DESIGN + PLANNING Tel: 250.591.1976 www.gemelladesign.com Jessica@shawbiz.ca

Project: GNP17 ENG01365/BP123009 Date: OCT. 2017 Drawn: JG Checked: JG Scale: NOTED

RDN DWG. No. GN-L-GEN-221







## IRRIGATION EQUIPMENT LEGEND

SYMBOL	MANUFACTURER	MODEL	DESCRIPTION
•	HUNTER	ICV-101G	I" (25mm) ELECTRIC REMOTE CONTROL VALVE TO BE INSTALLED IN A MOULDED STRUCTURAL FOAM VALVE BOX WITH BOLT DOWN COVER PER DETAIL E/I-2 AND MANUFACTURER'S RECOMMENDATIONS.
lacktriangle	HUNTER	ICZ-101-40	I" (25mm) DRIP ZONE CONTROL KIT WITH ELECTRIC REMOTE CONTROL VALVE, WYE FILTER AND PRESSURE REGULATOR TO BE INSTALLED IN A MOULDED STRUCTURAL FOAM VALVE BOX IWTH BOLT DOWN COVER, REFER TO DETAIL D/I-2. SIZE PER PLAN.
M	NIBCO	TII3	LINE-SIZE BRONZE GATE VALVE IN VALVE BOX WITH WITH BOLT DOWN COVER, REFER TO DETAIL B/I-2
BF	HUNTER	007	I" (25mm) DOUBLE CHECK VALVE BACKFLOW PREVENTER TO INSTALLED DOWNSTREAM OF WATER CHAMBER PER MANUFACTURER'S RECOMMENDATIONS AND PER DETAIL A/I-2.
C	HUNTER	NODE-600	G-STATION BATTERY OPERATED IRRIGATION CONTROLLER MOUNTED IN ZONE C I VALVE BOX PER MANUFACTURER'S RECOMMENDATIONS.
(AVR)	NDS	AVRV 50	AIR VACUUM RELEASE VALVE, INSTALL PER DETAIL J/I-2
(FV)	HUNTER	PLD BV	FLUSH VALVE, INSTALL PER DETAIL K/I-2
		CLASS 200	PVC LATERAL LINE, 3/4" (19mm) UNLESS NOTED OTHERWISE AT THE BEGINNING AND END OF EACH LENGTH OF PIPE, REFER TO DETAIL C/1-2
		SCHEDULE 40	I" (25mm) PVC MAINLINE, REFER TO DETAIL C/I-2

O.O GPM GALLONS PER MINUTE LAWN SPRAY - ZONE DESCRIPTION

-----VALVE SIZE

## IRRIGATION SPRINKLER LEGEND - REFER TO DETAIL F/1-2

SYMBOL	MFR	MODEL	PATTERN	RADIUS ft/m	FLOW RATE @ 40 PSI / 2.76bar GPM (l/m)
$\overline{\nabla}$		PROS-12-PRS40-CV-MP2000-90	90° - 210°	13-20 / 4-6	0.43-0.86 (1.6-3.3)
<b>∀</b>	HUNTER	PROS-12-PRS40-CV-MP2000-210 PROS-12-PRS40-CV-MP2000-360	360°	13-20 / 4-6 13-20 / 4-6	0.86-1.10 (3.3-4.2) 1.48 (5.6)

## IRRIGATION DRIPLINE LEGEND - REFER TO DETAILS G - K/1-2

SYMBOL	MAKE	MODEL	MAX. LENGTH OF RUN ft / m		EMITTER SPACING ft / m	FLOW RATE @ 40 PSI / 2.75 bar GPH (I/h)
E====3	NDS	SFCV-BR-1712	460 / 140	0.45	1.0/0.3	0.6 (2.27)

## IRRIGATION NOTES

- I. REFER TO TREE REPLACEMENT AND RIPARIAN ENHANCEMENT FOR GNPCC FRONTAGE WORKS REPORT PREPARED BY ENVIRONMENTAL DYNAMICS INC. (EDI) DATED MARCH 20, 2020 FOR ALL RIPARIAN AREA TREE AND VEGETATION REMOVAL AND REPLACEMENT SPECIFICATIONS AND PROCEDURES.
- 2. IRRIGATION SYSTEM INSTALLATION AND MAINTENANCE SHALL MEET OR EXCEED THE THE REQUIREMENTS SET OUT IN SECTION 5 - IRRIGATION SYSTEMS OF THE CANADIAN NURSERY LANDSCAPE ASSOCIATION (CNLA)/ CANADIAN SOCIETY OF LANDSCAPE ARCHITECTS (CSLA) CANADIAN LANDSCAPE STANDARD AND THE IRRIGATION DETAILS.
- 3. THE IRRIGATION SYSTEM IS DESIGNED TO OPERATE WITH A MINIMUM STATIC PRESSURE OF 110 PSI. THE MAXIMUM FLOW DEMAND FOR THE SYSTEM IS 12 GPM.
- 4. THE IRRIGATION PLAN IS DIAGRAMMATIC. NO IRRIGATION MAINLINE OR LATERAL LINE SHALL BE INSTALLED BEYOND ANY KNOWN LIMIT OF WORK, PROPERTY LINE OR ROAD RIGHT-OF-WAY. ALL EQUIPMENT AND PIPING SHALL BE INSTALLED WITHIN PLANTING AREAS.
- 5. THE CONTRACTOR SHALL ADJUST THE PLACEMENT AND RADIUS OF SPRINKLERS AS REQUIRED BY FIELD CONDITIONS TO ACHIEVE FULL COVERAGE OF ALL PLANTED AREAS AND TO MINIMIZE OVER-SPRAY ONTO ADJACENT HARD SURFACES, FENCES AND PROPERTY LINES.
- 6. OPERATE IRRIGATION CONTROLLERS WITHIN THE CITY OF NANAIMO WATER RESTRICTION SCHEDULE.
- 7. THE CONTRACTOR SHALL PROVIDE, INSTALL AND PROGRAM THE BATTERY OPERATED CONTROLLER AND ALL CONTROL WIRE.
- 8. THE CONTRACTOR SHALL BE RESPONSIBLE FOR REPAIRING OR REPLACING ALL EXISTING SPRINKLER EQUIPMENT OR PROPERTY TO REMAIN DAMAGED BY CONSTRUCTION OPERATIONS.
- 9. THE CONTRACTOR SHALL COORDINATE ALL WORK WITH OTHER TRADES TO ENSURE PROGRESS OF WORK IS NOT INTERRUPTED AND CAN BE COMPLETED IN A TIMELY MANNER.
- INSTALL SPRINKLER HEADS PERPENDICULAR TO SLOPES OR GRADE.
- 1. ALL EQUIPMENT MAKES AND MODELS SHALL BE PER THE IRRIGATION LEGEND OR APPROVED EQUAL. CONTACT THE LANDSCAPE ARCHITECT IN WRITING PRIOR TO PURCHASE FOR SUBSTITUTIONS.
- 12. THE LANDSCAPE ARCHITECT CANNOT PROVIDE ASSURANCES FOR WORK WITHOUT THE FOLLOWING FIELD REVIEW ATTENDANCE:
  - A. REVIEW OF UNCOVERED PRESSURIZED IRRIGATION MAINLINE AND LATERALS. B. REVIEW OF COMPLETE IRRIGATION INSTALLATION AND COVERAGE.

# • —


# ntag Nanaimo **District** 0 S

IRRIGATION

PLAN

NOTES	26MAR2020 Issued for Tender				
Date	26MAR2020				
#	0				

00THIS DRAWING IS NOT FINAL AND SHALL NOT BE USED FOR CONSTRUCTION WORK UNTIL IT HAS BEEN STAMPED AND SIGNED BY THE LANDSCAPE ARCHITECT THE COPYRIGHTS TO ALL DESIGNS AND DRAWINGS ARE THE PROPERTY OF MACDONALD GRAY CONSULTANTS. REPRODUCTION OR USE FOR ANY PURPOSE OTHER THAN THAT AUTHORIZED BY MACDONALD GRAY CONSULTANTS IS FORBIDDEN



(8) FLUSH VALVE PLUMBED TO PVC EXHAUST HEADER, REFER TO

PLANTING PLANS FOR ADDITIONAL

Not To Scale

DETAIL K/I2

INFORMATION.

END FEED LAYOUT


CENTRE FEED LAYOUT

I. REFER TO IRRIGATION AND

2. INSTALL PER MANUFACTURER'S

RECOMMENDATIONS.

(I) PIPE FROM POINT OF



4—

VALVE BOX WITH BOLT DOWN

(2) LINE-SIZED GATE VALVE, REFER TO IRRIGATION LEGEND

(3) SCH. 40 PVC MALE ADAPTOR TYP. OF (2) PLACES

(4) PVC MAINLINE PIPE, REFER TO IRRIGATION PLAN

(5) BRICK, (4) PLACES

(6) 4" (100mm) MIN. DEPTH OF 3/4" (19mm) MINUS WASHED GRAVEL

I. USE TEFLON TAPE ON ALL THREADED FITTINGS

2. REFER TO IRRIGATION PLANS AND LEGEND FOR ADDITIONAL INFORMATION.

Gate Valve Not to Scale Section

(2) ID TAG

3 WATER PROOF CONNECTION, TYP. OF (2) PLACES

VALVE BOX WITH BOLT DOWN

(4) 30" (0.75m) LINEAR LENGTH OF WIRE, COILED

(5) FINISH GRADE / TOP OF MULCH (6) REMOTE CONTROL VALVE, SIZE AS INDICATED ON PLAN. REFER

(7) PVC SCH. 80 NIPPLE (CLOSE) 8 PVC SCH. 40 ELL

TO IRRIGATION LEGEND.

9 PVC SCH. 80 NIPPLE, LENGTH AS REQUIRED

PVC SCH. 80 NIPPLE (2" [50mm] LENGTH, HIDDEN) AND SCH. 40

(II) PVC SCH. 40 TEE OR ELL (12) PVC LATERAL PIPE

(13) 4" (100mm) MIN. DEPTH OF 3/4" (19mm) MINUS WASHED GRAVEL

(14) BRICK, TYP. OF (4) PLACES

(15) PVC MAINLINE PIPE, REFER TO

IRRIGATION PLAN

Not to Scale

DRIPLINE TUBING: INSIDE RING O.6m DIA. OUTSIDE RING 1.2m DIA

2 TREE STEM

3 START CONNECTION (LATERAL TO DRIPLINE), REFER TO DETAIL 1/12

(4) DRIPLINE TEE

5 TUBING STAKE AS REQUIRED TO TIE DOWN DRIPLINE

6 FLUSH VALVE, REFER TO IRRIGATION PLAN AND DETAIL

7 AIR RELIEF VALVE, REFER TO IRRIGATION PLAN AND DETAIL J/I2


8 LATERAL LINE, REFER TO IRRIGATION PLAN

I. REFER TO IRRIGATION AND PLAN AND LEGEND FOR ADDITIONAL INFORMATION.

ripline at Tree Locations

Electric Remote Control Valve

Not to Scale



(2) DRIPLINE TUBING

(3) FINISHED GRADE (4) DRIPLINE TEE (BARB x BARB)

(6) DRIPLINE ADAPTOR (BARB X

ADDITIONAL INFORMATION. 2. INSTALL PER MANUFACTURER'S RECOMMENDATIONS.

Dripline Start Connection Not To Scale

SURFACE MATERIAL TO MATCH ADJACENT LANDSCAPE AREAS (2) COMPACTED BACKFILL TO MATCH ADJACENT BACKFILL BELOW REQUIRED DEPTH OF GROWING MEDIUM IN

LANDSCAPE AREAS 3 PVC PIPE, REFER TO IRRIGATION

(4) COMPACTED BEDDING MATERIAL HAND-PLACED 50mm (2") MIN. ON ALL SIDES OF PIPE. BEDDING MATERIAL TO BE FREE OF ROCKS, OTHER DELETERIOUS

NOTES: PARALLEL PIPES TO BE MIN. 50mm HORIZONTAL DISTANCE APART.

MATERIAL

2. IRRIGATION PIPING TO BE SEPARATED A MIN. OF 300mm FROM ELECTRICAL \$ OTHER UTILITIES.

Not to Scale

Pop-up Spray Head

3)—

4—

5)—

TOP OF MULCH IN PLANTING AREAS

(2) POP-UP SPRAY SPRINKLER

3) DO NOT USE SIDE INLET 4 PVC SCH. 80 NIPPLE, LENGTH AS

REQUIRED 5 PVC SCH. 40 ELL AND PVC SCH. 40 STREET ELL

6 PVC SCH. 40 STREET ELL

7) PVC SCH. 40 TEE OR ELL

8 PVC LATERAL PIPE, REFER TO IRRIGATION PLAN

I. REFER TO IRRIGATION PLAN, LEGEND AND NOTES FOR ADDITIONAL INFORMATION.

Not to Scale

TOP OF MULCH 2 IO" (250mm) ROUND VALVE BOX (3) AIR RELIEF VALVE AT HIGH POINT OF SYSTEM 4) 3/4" (19mm) MPT X 1/2" (13mm) FPT BUSHING (5) DRIPLINE TUBING (6) ADAPTOR TEE 7 BRICK SUPPORTS 8 100mm DEPTH 3/4" (19mm) GRAVEL SUMP NOTES: I. REFER TO IRRIGATION PLAN, LEGEND AND NOTES FOR ADDITIONAL INFORMATION.

Dripline Air Relief Valve

Not To Scale

(I) TOP OF MULCH

(2) IO" (250mm) ROUND VALVE BOX

POINT OF SYSTEM, REFER TO

(3) LINE FLUSHING VALVE AT LOW

5) BRICK SUPPORTS, (4) PER BOX

(6) 100mm DEPTH 3/4" (19mm)

REFER TO IRRIGATION PLAN,

LEGEND AND NOTES FOR


ADDITIONAL INFORMATION.

Not To Scale

GRAVEL SUMP

IRRIGATION LEGEND

(4) BLANK DRIPLINE TUBING



Dripline Flush Valve

**DETAILS** IRRIGATION

 $\Box$ 

O

00

O

THIS DRAWING IS NOT FINAL AND SHALL NOT BE USED

FOR CONSTRUCTION WORK UNTIL IT HAS BEEN

STAMPED AND SIGNED BY THE LANDSCAPE ARCHITECT

THE COPYRIGHTS TO ALL DESIGNS AND DRAWINGS ARE THE PROPERTY OF MACDONALD GRAY CONSULTANTS. REPRODUCTION OR USE FOR ANY PURPOSE OTHER THAN THAT AUTHORIZED BY MACDONALD GRAY

CONSULTANTS IS FORBIDDEN

anaimo

0

stric

B

0

S

O

 $\mathbf{B}$ 

• —

**D** 

• —

Q

D

Q

DO

D